

AUG 23 2006

AMENDMENTS TO THE CLAIMS

1. (Presently Amended) A vehicle accessory mount adapted for attachment to a handle-barred vehicle control bracket, comprising:
a body;
a pair of parallel mounting holes in the body;
the mounting holes aligned with portals in the control bracket;
a radial relief located between the parallel mounting holes; ~~and~~;
a threaded accessory hole[[.]] ; and;
wherein the radial relief is engageable with the control bracket.
2. (Original) The vehicle accessory mount of Claim 1, each mounting hole further comprising:
a cylinder portion; and,
a countersink portion that is larger in diameter than the cylinder portion.
3. (Previously Amended) The vehicle accessory mount of Claim 1, further comprising:
wherein the body is generally rectangular.
4. (Previously Amended) The vehicle accessory mount of Claim 1, further comprising:
wherein the threaded accessory hole is located between the mounting holes.
5. (Previously Amended) The vehicle accessory mount of Claim 1, further comprising:
wherein the threaded accessory hole is located in substantially perpendicular relationship
to the mounting holes.
6. (Original) The vehicle accessory mount of Claim 1, further comprising:
a ball stud attached to the threaded accessory hole.
7. (Original) A vehicle accessory mount, comprising:
a body;

a pair of parallel mounting holes in the body; and,
a ball stud attached to the body.

8. (Presently Amended) A vehicle accessory mount adapted for attachment to a handle-barred vehicle control bracket, comprising:
a body;
a pair of parallel mounting holes in the body;
the mounting holes aligned with portals in the control bracket;
a pair of hollow standoffs locatable between the mounting holes and bolt portals in the control bracket; and,
a threaded accessory hole.
9. (Previously Amended) The vehicle accessory mount of Claim 8, further comprising:
wherein the body is generally rectangular.
10. (Original) The vehicle accessory mount of Claim 8, the body further comprising:
a radial relief located between the parallel mounting holes.
11. (Previously Amended) The vehicle accessory mount of Claim 8, further comprising:
wherein the threaded accessory hole is located between the mounting holes.
12. (Previously Amended) The vehicle accessory mount of Claim 8, further comprising:
wherein the threaded accessory hole is located in substantially perpendicular relationship to the mounting holes.
13. (Original) The vehicle accessory mount of Claim 8, each mounting hole further comprising:
a cylinder portion; and,
a countersink portion that is larger in diameter than the cylinder portion.
14. (Previously Amended) The vehicle accessory mount of Claim 8, further comprising:

wherein the inside diameter of each hollow standoff is substantially the same as the inside diameter of the cylinder portion of the mounting holes.

15. (Presently Amended) A vehicle accessory mount adapted for attachment to a handle-barred vehicle control bracket, comprising:
- a body;
 - a pair of parallel mounting holes in the body;
 - the mounting holes aligned with portals in the control bracket;
 - a pair of hollow standoffs locatable between the mounting holes and the portals; and,
 - a ball stud attached to the body.